

88" OPEN ATV TRAILERS

102", 10', 12', 14', 18'



102", 10', 12', 14', 18'

STANDARD FEATURES

- > All Aluminum Construction
- > 24" O/C Crossmembers
- > 2"x3" Subframe Tubing
- > Torsion Ride Axles
- > Removable Ramps/Side Panels
- > 1/2" Marine Tech Plywood Decking
- > Rear Edge Protector
- > 4-Way Flat Power Connection
- > Recessed LED Marker Lights
- > 3500# Wishbone Style Coupler w/2" Ball
- > (2) 5000# Safety Chains
- > 1-Year Limited Warranty

STANDARD SPECIFICATIONS

| TRAILER MODEL | 88X102 | 88X10 | 88X12 | 88X14 | 88X18 |
|-----------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| Model Number | HATV88X102W | HATV88X10W | HATV88X12W | HATV88X14W | HATV88X18W |
| Deck (WxL) | 88"x102" | 88"x120" | 88"x144" | 88"x168" | 88"x216" |
| Overall (WxL) | 92"x12'6" | 92"x14' | 92"x16' | 92"x18' | 92"x22' |
| Deck Height | 23 1/2" | 23 1/2" | 23 1/2" | 23 1/2" | 23 1/2" |
| Hitch Height | 18" | 18" | 18" | 18" | 18" |
| Surface Mount D-Rings | 4 | 4 | 6 | 6 | 6 |
| Axle(s) - Qty/Rating | 1-2200# Idler | 1-2200# Idler | 1-3500# Idler | 1-3500# Idler | 2-2200# Braked |
| Wheels | 12" E-Rated Silver Mod | 12" E-Rated Silver Mod | 12" E-Rated Silver Mod | 12" E-Rated Silver Mod | 12" E-Rated Silver Mod |
| Tires | ST145/R12E | ST145/R12E | ST145/R12E | ST145/R12E | ST145/R12E |
| GVWR | 2200# | 2200# | 2990# | 2990# | 4000# |
| Curb Weight | 380# | 430# | 450# | 475# | 835# |
| Payload | 1820# | 1770# | 2540# | 2515# | 3565# |
| Wheel Jack | TBD | TBD | 1200# | 1200# | 1200# |
| Power Connection | 4-Way Flat | 4-Way Flat | 4-Way Flat | 4-Way Flat | 7-Way Round |

OPTIONS & ACCESSORIES

| CONSTRUCTION OPTIONS |
|---|
| Upgrade to Extruded Aluminum Decking |
| TIRE/WHEEL ASSEMBLIES & ACCESSORIES |
| Upgrade to 13" Silver Mod Wheels (From 12" E-Rated Silver Mod) |
| Upgrade to 15" Silver Mod (From 12" E-Rated Wheels, Includes Drop Tongue) |
| Spare 12" Silver Mod Wheel w/ 145/R12 Tire |
| Spare 13" Silver Mod Wheel w/ 175/80R13 Tire |
| Spare 15" Silver Mod Wheel w/ 205/75R15 Tire |
| Upgrade to 12" Aluminum Spoke Wheels (145/R12 Tire; From 12" Silver Mod) |
| Upgrade to 13" Aluminum (Radial; From 13" Silver Mod Wheels) |
| Upgrade to 15" Aluminum (Radial; From 15" Silver Mod Radial Wheels) |
| Bolt-On Spare Tire Carrier (Tongue-Mounted) |

| AXLE OPTIONS |
|---|
| Upgrade to 2-2K Torsion Idler Axles (From 1-3K Idler; 14' Model, 2990 GVWR) |
| Upgrade to 2-2K Torsion Braked Axles (From 1-3K Torsion Idler, 14' Model) |
| RAMP OPTIONS |
| Side Load Ramps Upgrade (102") |
| Side Load Ramps Upgrade (120") |
| Side Load Ramps Upgrade (14') |
| Side Load Ramps Upgrade (18') |
| TIE-DOWN OPTIONS |
| Light Duty Surface-Mounted D-Ring (Installed) |
| Heavy Duty Recessed D-Rings |
| ACCESSORIES |
| Add 1200# Tongue-Mounted Wheel Jack |
| Stabilizer Jacks (Installed; Pair) |



RAMP CAPACITY BY MODEL

| Ramp Type | Applicable Models | Capacity |
|--|--|--------------|
| Utility Trailer Rear Ramp (Fold-Down) | SSR (All Sizes), AR 2.0 (All Sizes), WR 2.0 (All Sizes), FA 2.0 (All Sizes), Landscape 2.0 (All Sizes) | 750# |
| Utility Trailer Rear Ramp (Fold-Down Bi-Fold) | SSR (Optional, All Sizes), AR 2.0 (Optional, All Sizes), WR 2.0 (Optional, All Sizes), FA 2.0 (Optional, All Sizes), Landscape 2.0 (Optional, All Sizes) | 750# |
| Deckover Equipment Trailer Ramps (Stow) | (All Sizes) | 4000# (Pair) |
| Deckover Equipment Trailer Ramps 14K (Fold-Down) | (All Sizes) | 5000# (Pair) |
| Patriot Ramps (Fold-Down) | Stowaway 6' Aluminum Ramps | 4000# (Pair) |
| Patriot Ramps 14K (Fold-Down) | (All Sizes) | 5000# (Pair) |
| Dump Trailers (Side-Stow, Optional) | (All Sizes) | 4000# (Pair) |
| ATV (83" Wide, Side-Stow) | (All Sizes) | 1200# (Pair) |
| ATV (88" Wide, Side-Stow) | (All Sizes) | 750# (Pair) |
| Open Motorcycle (Rear-Stow) | (All Sizes) | 1200# |
| Slingshot Rear Ramp (Fold-Down Bi-Fold) | HU-SLINGSHOT | 1500# |
| Open Car Hauler 2.0 (Stow) | (All Sizes) | 4000# (Pair) |
| Open Car Hauler 2.0-10K (Stow) | (All Sizes) | 4000# (Pair) |
| Open Car Hauler Standard (Stow) | (All Sizes) | 4000# (Pair) |
| Open Snow (Rear Stow) | HFS | 750# |
| Sport Deck (Rear Stow, Telescoping) | HFS | 1000# |
| Enclosed Cargo (4', 5', 6' Wide) | (All Sizes) | 1500# |
| Enclosed Cargo (7', 7.5' Wide) | (All Sizes) | 1500# |
| Enclosed Cargo (8.5' Wide, Premium) | (All Sizes) | 1500# |
| Enclosed Motorcycle (7' Wide) | (All Sizes) | 1500# |
| Enclosed Car Hauler (8.5' Wide) | (All Sizes) | 4000# |
| Enclosed Gooseneck (8.5' Wide, Rear) | (All Sizes) | 4000# |
| Enclosed Gooseneck (8.5' Wide, Side, Optional) | (All Sizes) | 1200# |
| Enclosed Snowmobile (7', 7.5', 101" Wide, Rear) | (All Sizes) | 1500# |
| Enclosed Snowmobile (7', 7.5', 101" Wide, Front) | (All Sizes) | 1200# |
| Enclosed Snowmobile (Crossover, Rear) | (All Sizes) | 1500# |



TONGUE EXTENSION BY MODEL

| Trailer Type | Allowable Extension | Additional Requirements | Item Number | Description |
|---|-------------------------|--|---------------|--|
| Enclosed Cargo (4' & 5' Wide) | N/A | Frame Upgrade Required; Consult Engineering | N/A | N/A |
| Enclosed Cargo (6', 7', 7.5' Wide) | 12" | Economy Models Require Center Beam Upgrade | TONGUE12EXT | 12" Extended Tongue (For 3K Tandem Axle Enclosed w/2"x5" Frame) Includes Center Beam Upgrade; Not Available w/All Sport or Snow Trailers |
| Enclosed Cargo (8.5'-Wide, Premium) | 12" (16" w/ Upgrade) | Minimum 6" Frame For 16" Tongue Extension; Upgrade May Be Required | TONGUE12EXT | 12" Extended Tongue (For 3K Tandem Axle Enclosed w/2"x5" Frame) Includes Center Beam Upgrade; Not Available w/All Sport or Snow Trailers |
| Enclosed Motorcycle (7' Wide) | 12" | | TONGUE12EXT | 12" Extended Tongue (For 3K Tandem Axle Enclosed w/2"x5" Frame) Includes Center Beam Upgrade; Not Available w/All Sport or Snow Trailers |
| Enclosed Car Hauler (8.5' Wide, Premium) | 16" | | TONGUE16EXTCH | 16" Extended Tongue (For 5K Tandem Axle Enclosed; Trailer Must Have 2"x6" Frame or Larger) Not Available w/All Sport or Snow Trailers |
| Enclosed Car Hauler All Sport (8.5' Wide) | N/A | Extended Tongue Incompatible w/Front Ramp | N/A | N/A |
| Enclosed Snowmobile (7' & 7.5' Wide) | N/A | Extended Tongue Incompatible w/Front Ramp | N/A | N/A |
| Enclosed Snowmobile (101" Wide) | 10" | Requires 3"x5" Tongue Upgrade w/Straight-Pull Coupler | TBD | TBD |

**Please note that all 5k tandem trailers w/extended tongues require a minimum of 6" base frame, regardless of brand/model