

TILTING OPEN CAR HAULERS

18', 20', 22'



101" WIDE

STANDARD FEATURES

- All Aluminum Construction
- 2"x3" Heavy Wall Crossmembers (16" O/C)
- 2"x6" Subframe Tubing (Outer & Tongue)
- 12500# Coupler w/ 2-5/16" Ball
- (2) 7800# Safety Chains
- 5000# Wheel Jack
- Dexter Torsion Ride Axles
- Extruded Aluminum Decking
- (4) 5000# Recessed D-Rings
- Fixed 2"x2" Front Bumper
- Removable Aluminum Fender (D/S)
- Hydraulic Tilt System w/Control Valve
- Front 18" Stationary Deck
- Recessed LED Marker Lights
- Limited Lifetime Warranty

STANDARD SPECIFICATIONS

TRAILER MODEL	18'	20'	22'
Model Number	HOCH8X18TILT	HOCH8X20TILT	HOCH8X22TILT
Deck (WxL)	80"x16'	80"x18'	80"x20'
Overall (WxL)	101"x20'4"	101"x22'4"	101"x24'4"
Deck Height	17"	17"	17"
Hitch Height	18"	18"	18"
Decking	Extruded Aluminum	Extruded Aluminum	Extruded Aluminum
Axle(s) - Qty/Rating	2-3500#	2-3500#	2-3500#
Wheels	15" Aluminum	15" Aluminum	15" Aluminum
Tires	205/75R15	205/75R15	205/75R15
GVWR	7250#	7250#	7250#
Curb Weight	1160#	1400#	1580#
Payload	6090#	5850#	5670#
Power Connection	7-Way Round	7-Way Round	7-Way Round

OPTIONS & ACCESSORIES

CONSTRUCTION OPTIONS	TIRE/WHEEL ASSEMBLIES & ACCESSORIES
Upgrade to 3" Adjustable 2-5/16" A-Frame Coupler	Spare 15" Silver Mod Wheel w/ 205/75R15 Tire
Upgrade to Removable Curbside Fender	Spare 15" Aluminum Wheel w/ 205/75R15 Tire
Gooseneck Upgrade for Open Trailers	Spare 15" Silver Mod Wheel w/ 225/75R15 Tire (6-Lug)
Heavy Duty Rub Rail with Stake Pockets (PBF)	Spare 15" Aluminum Wheel w/ 225/75R15 Tire (6-Lug)
Upgrade Cylinders & Hoses (On Tilting Open Car Hauler for 6K & 7K Axles)	Bolt-On Spare Tire Carrier (Tongue-Mounted)
ACCESSORIES	TIE-DOWN OPTIONS
Air Dam for Open Car Hauler	5000# Recessed Heavy Duty D-Ring w/Backing Plate (Installed)
Large, Lockable Tongue-Mounted Diamond Plate Toolbox (Requires Wishbone Tongue)	Zinc 6000# Recessed Swivel D-Ring w/Backing Plate (Installed)
AXLE OPTIONS	Upgrade to Zinc 6000# Recessed Swivel D-Rings (From 5000# Recessed HD D-Ring w/Backing Plate; Installed)
Upgrade to 2-5K Torsion Braked Axles (From 2-3K Braked)	Adjustable Wheel Chock for Open Trailers (Set of 2; 24" Adjustable w/Airline Track)
Upgrade to 2-7K Torsion Braked Axles (From 2-5K Braked; Includes 16" Tire Upgrade; 2x8 Frame Upgrade Required)	JACKS & JACK ACCESSORIES
	Upgrade to 8000# Pedestal Jack (From 1500# Wheel Jack)



RAMP CAPACITY BY MODEL

Ramp Type	Applicable Models	Capacity
Utility Trailer Rear Ramp (Fold-Down)	SSR (All Sizes), AR 2.0 (All Sizes), WR 2.0 (All Sizes), FA 2.0 (All Sizes), Landscape 2.0 (All Sizes)	750#
Utility Trailer Rear Ramp (Fold-Down Bi-Fold)	SSR (Optional, All Sizes), AR 2.0 (Optional, All Sizes), WR 2.0 (Optional, All Sizes), FA 2.0 (Optional, All Sizes), Landscape 2.0 (Optional, All Sizes)	750#
Deckover Equipment Trailer Ramps (Stow)	(All Sizes)	4000# (Pair)
Deckover Equipment Trailer Ramps 14K (Fold-Down)	(All Sizes)	5000# (Pair)
Patriot Ramps (Fold-Down)	Stowaway 6' Aluminum Ramps	4000# (Pair)
Patriot Ramps 14K (Fold-Down)	(All Sizes)	5000# (Pair)
Dump Trailers (Side-Stow, Optional)	(All Sizes)	4000# (Pair)
ATV (83" Wide, Side-Stow)	(All Sizes)	1200# (Pair)
ATV (88" Wide, Side-Stow)	(All Sizes)	750# (Pair)
Open Motorcycle (Rear-Stow)	(All Sizes)	1200#
Slingshot Rear Ramp (Fold-Down Bi-Fold)	HU-SLINGSHOT	1500#
Open Car Hauler 2.0 (Stow)	(All Sizes)	4000# (Pair)
Open Car Hauler 2.0-10K (Stow)	(All Sizes)	4000# (Pair)
Open Car Hauler Standard (Stow)	(All Sizes)	4000# (Pair)
Open Snow (Rear Stow)	HFS	750#
Sport Deck (Rear Stow, Telescoping)	HFS	1000#
Enclosed Cargo (4', 5', 6' Wide)	(All Sizes)	1500#
Enclosed Cargo (7', 7.5' Wide)	(All Sizes)	1500#
Enclosed Cargo (8.5' Wide, Premium)	(All Sizes)	1500#
Enclosed Motorcycle (7' Wide)	(All Sizes)	1500#
Enclosed Car Hauler (8.5' Wide)	(All Sizes)	4000#
Enclosed Gooseneck (8.5' Wide, Rear)	(All Sizes)	4000#
Enclosed Gooseneck (8.5' Wide, Side, Optional)	(All Sizes)	1200#
Enclosed Snowmobile (7', 7.5', 101" Wide, Rear)	(All Sizes)	1500#
Enclosed Snowmobile (7', 7.5', 101" Wide, Front)	(All Sizes)	1200#
Enclosed Snowmobile (Crossover, Rear)	(All Sizes)	1500#