

RAFT TRAILERS

10' & 12'



10' & 12'

STANDARD FEATURES

- > All Aluminum Construction
- > 24" O/C Floor Crossmembers
- > 2"x3" Subframe Tubing
- > 6000# Straight Coupler w/2" Ball
- > (2) 5000# Safety Chains
- > Dexter Torsion Ride Axles
- > 5/4" Pressure Treated Decking
- > Rear Roller w/Bearings
- > Manual Winch w/24" Post
- > (5) Tie-Down Points Per Side
- > (2) Front Tie-Down Points
- > Recessed LED Marker Lights
- > 4-Year Limited Warranty

STANDARD SPECIFICATIONS

TRAILER MODEL	10'	12'
Model Number	HRFT84x10	HRFT84x12
Deck (WxL)	84"x10'	84"x12'
Overall (WxL)	84"x14'	84"x16'
Deck Height	26"	26"
Hitch Height	21"	21"
Axle(s) - Qty/Rating	1-2200# Idler	1-2200# Idler
Wheels	13" Silver Mods	13" Silver Mods
Tires	175/80R13	175/80R13
GVWR	2200#	2200#
Curb Weight	540#	590#
Payload	1660#	1610#
Power Connection	4-Way Flat	4-Way Flat

OPTIONS & ACCESSORIES

TIRE/WHEEL ASSEMBLIES & ACCESSORIES	FLOORING OPTIONS
Spare 13" Silver Mod Wheel w/ 175/80R13 Tire	Upgrade to 3/4" Quad-Ply Decking (Non-Skid Surface, FRP Backer; PBF)
Upgrade to 13" Aluminum (Radial; From 13" Silver Mod Wheels)	TIE-DOWN OPTIONS
Bolt-On Spare Tire Carrier (Tongue-Mounted)	D-Rings for Raft Trailer (Bolt-On)
CONSTRUCTION OPTIONS	Welded Side Tie-Down Ring
Tilt Bed Option (Pin System)	Light Duty Surface-Mounted D-Ring (Installed)
Anti-Rattle Tilt Bed Option	ACCESSORIES
Upgrade to 36" Winch Post (Replaces 24" Winch Post)	Add 1200# Tongue-Mounted Wheel Jack